



# Model 9300 Weight Indicator

- 6-digit display
- 60,000 display graduations
- Powers up to 8 load cells
- 15 Updates/second typical
- NEMA 4 stainless steel washdown enclosure
- Selectable primary/secondary units  
lb, kg, ounces, short tons, metric tons,  
grams or none.
- 2 Independent serial  
communications ports:  
(1) full duplex, (1) unidirectional or  
active 20 mA current loop
- Full front-panel digital calibration  
& configuration
- Three-stage digital filtering
- CE Marked



## SPECIFICATIONS

### ELECTRICAL

Excitation Voltage.....	10 ±0.5 VDC, 8 x 350Ω load cells or 16 x 700Ω load cells
-------------------------	--

### PERFORMANCE

Maximum Display Counts .....	100,000
Analog Signal Input Range.....	0.6 mV/V - 4.5 mV/V
Sensitivity.....	0.3μV/graduation min.
Measurement Rate .....	15 measurements/second

### ENVIRONMENTAL

Operating Temperature.....	14 to 122°F -10 to 50°C
----------------------------	----------------------------

### POWER

AC Power .....	115 OR 230 VAC 50-60 HZ
----------------	----------------------------

### MECHANICAL

Weight .....	6.4 lb (2.9 kg)
Enclosure .....	NEMA 4X/IP66 stainless steel
Enclosure Size .....	9.5 in x 6 in x 2.75 in
Display .....	6 digit LED

## OPTIONS

Analog output: selectable 0-10V,  
4-20 mA

Panel mount kit

Please specify if CE mark is required