



# Model 9390 Battery Powered Weight Indicator

- Large 1" high contrast LCD display
- 6-digits
- 100,000 graduations
- Powers up to 4 load cells
- Battery powered
- 15 updates/second typical
- Configurable standby mode for extended battery life
- Full front-panel digital calibration & configuration
- Three-stage digital filtering
- Full Duplex RS232



INSTRUMENTATION

## OPTIONS

Carrying case for portable use  
Please specify if CE mark is required

## SPECIFICATIONS

<b>ELECTRICAL</b>	
Excitation Voltage.....	5 ±0.5VDC, 4 x 350Ω load cells or 8 x 700Ω load cells
<b>PERFORMANCE</b>	
Maximum Display Counts .....	100,000
Analog Signal Input Range.....	4.5 mV/V
Sensitivity.....	0.3 μV/graduation min.
Measurement Rate .....	30, 15, 7.5, 3.75/second
<b>ENVIRONMENTAL</b>	
Operating Temperature.....	14 to 104°F -10 to 40°C
<b>POWER</b>	
Power.....	9 VDC provided by 6 "C" cells or included AC adaptor
<b>MECHANICAL</b>	
Weight .....	4.6 lb with batteries
Enclosure .....	NEMA 4X/IP66 stainless steel
Enclosure Size .....	9.0 in x 3 in x 5.52 in
Display .....	6 digit LCD, 1" high