





REVISIONS			
REV	DESCRIPTION	DATE	APPROVED

FORCE



COMPRESSION UPSCALE

LOAD CELL CHARACTERISTICS		U.S. CAPACITY
#	CAPACITY (lbf)	250
1	FLEXURE OVERALL HEIGHT	1.02 (25.9)
2	FLEXURE LENGTH	2.38 (60.5)
3	FLEXURE WIDTH	0.50 (12.8)
4	FLEXURE MOUNTING SURFACE LENGTH	0.97 (24.6)
5	MOUNT SURFACE TO FLEXURE BOTTOM	0.12 (3.0)
6	FLEXURE END HEIGHT	0.79 (20.1)
7	MOUNT & LOAD HOLE DIAMETER	0.17 (4.3)
8	MOUNTING HOLE OFFSET FROM EDGE	0.25 (6.4)
9	MOUNT HOLE TO FLEXURE EDGE	0.25 (6.4)
10	MOUNTING HOLE SPACING	0.50 (12.7)
11	MOUNT HOLE TO LOAD AXIS HOLE	1.31 (33.3)
12	COVER LENGTH	1.88 (47.8)
13	COVER WIDTH	0.75 (19.1)
14	COVER HEIGHT	0.99 (25.1)
15	RADIAL CLEARANCE AROUND LOAD HOLE	0.30 (7.6)
16	INTEGRAL CABLE BEND CLEARANCE	0.50 (12.7)
17	CABLE TYPE [3]	.13 (3.3) O.D. 4 CONDUCTOR 28 GAGE SHIELDED CABLE
18	IDENTIFICATION LABEL INCLUDING: MODEL, CAPACITY & SERIAL NUMBER	

- [3] STANDARD CABLE LENGTH IS 5 FT (1.5 M)
NON-STANDARD CABLE LENGTH PER OPTION CODE
2. DIMENSIONAL TOLERANCE: +/- 0.01 (mm +/- 0.3)
1. DIMENSIONS IN INCHES & (MM)

Interface, Inc.
7401 E. BUTHERUS DR. SCOTTSDALE, ARIZONA 85260

TITLE: OUTLINE MODEL: MB		DWG NO.: 80022	
SIZE: A	DRAWN BY: BKS	DATE: 8-9-95	REV:
SCALE: 1:1		APPROVED BY:	SHEET 1 OF 1

Interface Inc. claims propriety rights in the information disclosed heron. This drawing is furnished in confidence on the express understanding that neither it nor any reproduction thereof will be disclosed to others or used for the purpose of manufacture or procurement of the article or part shown heron without written permission of Interface Inc. The drawing shall remain Interface's property and shall be returned on Interface's request.